
LG-1039M

Metal Wall Sconce Surface Mount





Project Information:	Project Name:
Fixture Type:	Location:

SCONCE

Soft Edge Rectangle Wall Sconce

Geometric metal surface mount light fixture. Lighting technology meets precise design. Visual comfort in its purest form. Our Sconce light fixtures are powder coated white. SMD LED lighting panel is high performance, low power that provides outstanding reliability and color quality/consistency. 2700K and 3000K color temperatures are available with 90 CRI.

- Fixtures can be used with all Smart House Systems such as Lutron, Vantage, Control4, Crestron and others.
- Class 1 solution
- Damp location Rated
- 120V/277V
- SMD LED Included

Quick Info





Application				
New Construction / Remodeling				
Delivered Lumens	Color Quality			
220 lm (12W)	90 CRI, 3-step SDCM			
Color Temperature	Light Distribution			
2700K 3000K	Indirect			
Input Voltage	Dimming			
120/277V	TRIAC/ ELV			
Plate Powder coated metal plate				
Mounting	Module Ratings			
Universal mounting plate	Damp Location			
Guarantee	Additional Dimming Options			
40,000 hrs 3 years	0-10 / DALI Dimming / Lutron EcoSystem			

LG-1039M

Metal Wall Sconce Surface Mount

Project Information:	Project Name:
Fixture Type:	Location:

Ordering Guide

PRODUCT CODE

LG - 1039M

E	xaı	mp	ie i	Nur	nb	er

<u>LG-1039M</u> <u>CL2-18SMD</u> <u>30K 90 120 120-120V T</u>

Order Number

<u>LG-1039M</u> <u>CL2-18SMD</u> <u>90 120</u> _____

OUTPUT

* COLOR TEMPERATURE

□ CL2-18SMD (STANDARD) □ 30K - 3000K (STANDARD)

□ 27K - 2700K

CRI

90 - 90 CRI

BEAM SPREAD

■ 120° (STANDARD)

VOLTAGE

□ 120 - 120V (STANDARD)

■ 277 - 120/277V

DIMMING OPTION

□ T - Triac/ELV (STANDARD)

D - DAL

ECO - (Hi - lume Premier 0.1% Eco System LED Driver with Soft-on, Fade-to-black dimming technology)

□ 0 - 10

*Custom color temperature available upon request.

