


# LG-1042M

## Metal Wall Sconce Surface Mount



Project Information:	Project Name:
Fixture Type:	Location:

## SCONCE

### Round Wall Sconce

Geometric metal surface mount light fixture. Lighting technology meets precise design. Visual comfort in its purest form. Our Sconce light fixtures are powder coated white. SMD LED lighting panel is high performance, low power that provides outstanding reliability and color quality/consistency. 2700K and 3000K color temperatures are available with 90 CRI.

- Fixtures can be used with all Smart House Systems such as Lutron, Vantage, Control4, Crestron and others.
- Class 1 solution
- Damp location Rated
- 120V/277V
- SMD LED Included

## Quick Info



<b>Application</b> New Construction / Remodeling	
<b>Delivered Lumens</b> 350 lm (18W)	<b>Color Quality</b> 90 CRI, 3-step SDCM
<b>Color Temperature</b> 2700K 3000K	<b>Light Distribution</b> Indirect
<b>Input Voltage</b> 120/277V	<b>Dimming</b> TRIAC/ ELV
<b>Plate</b> Powder coated metal plate	
<b>Mounting</b> Universal mounting plate	<b>Module Ratings</b> Damp Location
<b>Guarantee</b> 40,000 hrs   3 years	<b>Additional Dimming Options</b> 0-10 / DALI Dimming / Lutron EcoSystem

# LG-1042M

Metal Wall Sconce  
Surface Mount

Project Information:	Project Name:
Fixture Type:	Location:

## Ordering Guide

### PRODUCT CODE

LG - 1042M

### Example Number

LG-1042M CL2-18SMD 30K 90 120 120-120V T

### Order Number

LG-1042M CL2-18SMD 90 120

### OUTPUT

CL2-18SMD (STANDARD)

### \* COLOR TEMPERATURE

30K - 3000K (STANDARD)

27K - 2700K

### CRI

90 - 90 CRI

### BEAM SPREAD

120° (STANDARD)

### VOLTAGE

120 - 120V (STANDARD)

277 - 120/277V

### DIMMING OPTION

T - Triac/ELV (STANDARD)

D - DALI

ECO - (Hi - lume Premier 0.1% Eco System LED Driver with Soft-on, Fade-to-black dimming technology)

0 - 10

\*Custom color temperature available upon request.