

LG-7010

Multiple 10 Cell Narrow Recessed Downlight LED



| | |
|----------------------|---------------|
| Project Information: | Project Name: |
| Fixture Type: | Location: |

NARROWLINE

Narrow Recessed Downlight LED - 1x10 Square

Revolutionary narrow recessed downlight available in slim trim or trimless. Its simplified retrofit installation can be used in both new and existing spaces.

LED lighting engine is high performance, low power that provides outstanding reliability and color quality/consistency. 2700K, 3000K, 3500K, and 4000K color temperatures are available with 95 CRI.

- Life Rated for 40,000 hours at 70% lumen maintenance
- All testing reports are based on published industry procedures

Quick Info



| | |
|--|---|
| Application New Construction / Remodeling | |
| Delivered Lumens Black Bevel - 1120lm (20W) 10x2W White Bevel - 1400lm (20W) 10x2W | Color Quality 95 CRI, 2-step SDCM |
| Color Temperature 2700K 3000K 3500K 4000K | Light Distribution General |
| Input Voltage 120/277V | Dimming TRIAC/ELV |
| Trims Slim Trim - Aluminum powder coated | Junction Box IC Rated - REMOTE |
| Housing Ratings N/A | Module Ratings <input checked="" type="checkbox"/> Wet Location |
| Guarantee 40,000 hrs 3 years | Additional Dimming Options 0-10 / DALI Dimming / Lutron EcoSystem |

LG-7010

Multiple 10 Cell Narrow
Recessed Downlight LED

| | |
|----------------------|---------------|
| Project Information: | Project Name: |
| Fixture Type: | Location: |

Ordering Guide

PRODUCT CODE

LG - 7010

MOUNTING (OPTIONAL)

- N - New Construction Mounting Plate

COLOR TEMPERATURE

- 27K - 2700K
- 30K - 3000K (STANDARD)
- 35K - 3500K
- 40K - 4000K

CRI

- 95 - 95 CRI

BEAM SPREAD

- 15 °
- 30 ° (STANDARD)
- 45 °

LENS OPTICAL

- SF - Soft Focus (STANDARD)
- FR - Frosted
- LI - Linear Spread
- PR - Prismatic

BEVEL COLOR

- BBL - Black (STANDARD)
- BWH - White

FRAME COLOR

- WH - White (STANDARD)
- BL - Black

DIMMING OPTION

- T - Triac/ELV (STANDARD)
- D - DALI
- ECO - (Hi - lume Premier 0.1% Eco System LED Driver with Soft-on, Fade-to-black dimming technology)
- 0 - 10

Example Number

LG-7010 N 30K 95 30 SF BBL WH I


Order Number

LG-7010 _ _ _ _ _

LG-7010

Multiple 10 Cell Narrow
Recessed Downlight LED

TRIM



| | |
|----------------------|---------------|
| Project Information: | Project Name: |
| Fixture Type: | Location: |

| | | |
|-------------------|---|-------|
| LED TYPE | LED OSRAM | |
| BEVEL | Black | White |
| DELIVERED LUMENS | 1120 | 1400 |
| WATTS | 10 x 2W | |
| CRI | 95 | |
| COLOR TEMPERATURE | 2700K / 3000K / 35000K / 4000K | |
| VOLTAGE | 120 V / 277 V | |
| DIMMING | <ul style="list-style-type: none"> • TRIAC /ELV (Down to > 1%) - STANDARD • 0 -10 v (Down to > 5%) • Lutron (Hi-lume Premier 0.1 % Eco System LED Driver with Soft-on, Fade-to-black dimming technology) (Install remote, no junction box supplied) • DALI (Install remote, no junction box supplied) | |
| POWER SUPPLY | Constant current driver 23.1-35V/600mA | |
| BEAM SPREAD | 15°/24°/38°/60° | |
| OPTICS | Soft Focus/ Frosted / Linear Spread/ Prismatic | |
| ADJUSTABILITY | Non Adjustable | |
| JUNCTION BOX | IC RATED - Remote | |
| FINISH | Aluminum Powder Coated | |

Product Features

- Revolutionary flush mounted slim trim design offers consistent aesthetics
- Energy efficient LED light engines
- Dimmable with a variety of commonly used drivers
- Fixtures can be used with all Smart House Systems such as Lutron, Vantage, Control4, Crestron and others
- Easy installation for new construction and remodel applications
- IC Rated UL approved fixtures
- Wet location rated
- Driver included

1003-10

New Construction Plate
For 7010 / 7010TL

