
# RQP-D35-120

**Square Pendant** 





# Quick Info

Application

Project Information:	Project Name:
Fixture Type:	Location:

# RONDO

### Square Pendant Ceiling Light

Innovative geometric ceiling light LED. Lighting technology meets precise design. Visual comfort in its purest form. Our Rondo ceiling lights are available recessed, surface mounted or pendant up to 48" wide. Complete with translucent acrylic diffuser for uniform light distribution. Rondo fixtures are powder coated white. Please inquire for custom colors.

LED lighting panel is high performance, low power that provides outstanding reliability and color quality/consistency. 2700K, 3000K, 3500K, 4000K and 6500K color temperatures are available with 90 CRI.

- Life Rated for 40,000 hours at 70% lumen maintenance
- Energy efficient LED
- · Easy installation for new construction and remodel applications
- 120/277 V
- Available in 5 different sizes from 13.8" to 48"



1700 lm (25W) / 3023 lm (40W) / 4700 lm (60W) / 9600 (120W) / 4700 (60W)       90 CRI, 2-step SDCM         Color Temperature       Light Distribution         2700K 5000K       General         3000K 6500K       Dimming         120/277V       D-10 (Internal driver)         Trims       Beam Spread         Aluminum powder coated       120°         N/A       Module Ratings         N/A       Damp Location	Delivered Lumens	Color Quality
2700K 3000K 6500K 3000K 6500K 3000K 6500KGeneralInput Voltage 120/277VDimming 0-10 (Internal driver)Trims Aluminum powder coatedBeam Spread 120°Housing RatingsModule Ratings	1700 lm (25W) / 3023 lm (40W) / 4700 lm (60W) / 9600 (120W) / 4700 (60W)	90 CRI, 2-step SDCM
3000K       6500K         3500K       4000K         Input Voltage       Dimming         120/277V       0-10 (Internal driver)         Trims       Beam Spread         Aluminum powder coated       120°         Housing Ratings       Module Ratings	Color Temperature	Light Distribution
120/277V     0-10 (Internal driver)       Trims Aluminum powder coated     Beam Spread 120°       Housing Ratings     Module Ratings	3000K 6500K 3500K	General
Trims     Beam Spread       Aluminum powder coated     120°       Housing Ratings     Module Ratings	Input Voltage	Dimming
Aluminum powder coated     120°       Housing Ratings     Module Ratings	120/277V	0-10 (Internal driver)
Housing Ratings Module Ratings	Trims	Beam Spread
	Aluminum powder coated	120°
N/A  O Damp Location	Housing Ratings	Module Ratings
	N/A	Damp Location



RQP-D35-120

**Square Pendant** 

Project Information:	Project Name:
Fixture Type:	Location:

## **Ordering Guide**

### **PRODUCT CODE - DIAMETER**

- RQP-D35 (13.8")
- **RQP-D45 (17.7")**
- **RQP-D60** (23.6")
- **RQP-D90 (35.4")**
- **RQP-D120 (47.2")**

#### COLOR TEMPERATURE

- **D** 27K 2700K
- **D** 30K 3000K
- **D** 35K 3500K
- **u** 40K 4000K
- **D** 50K 5000K
- □ 65K 6500K

#### **DIMMING OPTION**

**D** 0 - 10

#### \* Color

- WH White
- BL Black

\* Custom color upon request with a minimum order of 50 units

#### Example Number

RQP-D35 40K 0-10 WH

Order Number



RQP-D35-120

Square Pendant

Project Information:	Project Name:
Fixture Type:	Location:

### Sizes and Lumens

