



8165 E Kaiser Blvd. Anaheim, CA 92808  
www.lightlaboratory.com

Report No: L022111005



**Report No:** L022111005

**Issue Date:** 2/22/2021

**Report Prepared For:** Light and Green  
2340 E Olympic Blvd. Unit E., Los Angeles, CA 90021

**Model Number:** LG-1042-27K

**Test:** Photometric/Electrical Test

**Standards Used:** Appropriate part or all test guidelines were used for test performed:  
*IESNA LM79: 2008* Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products  
*ANSI NEMA ANSLG C78.377: 2008* Specification of the Chromaticity of Solid State Lighting Products  
*ANSI C82.77:2002:* Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

**Description of Sample:** Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

**Special Test Condition:** Fixture is tested with no special conditions.

**Sample Arrival Date:** 2/8/21

**Date of Tests:** 2/15/21 - 2/22/21

**Seasoning of Sample:** No seasoning was performed in accordance with IESNA LM-79.

**Equipment List**

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S4	1/9/22
BK PRECISION	1747	PS-DC04	1/10/22
Fluke Digital Thermometer	52K/J	MT-TP05	1/10/22
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

### General Information

<b>Manufacturer:</b>	Light and Green
<b>Model Number:</b>	LG-1042-27K
<b>Driver Model Number:</b>	ERP EBR020U-0500-42

### Photometric & Electrical Test Results

<b>Total Lumens:</b>	1087.70
<b>Efficacy:</b>	54.34
<b>Input Voltage (VAC/60Hz):</b>	120.02
<b>Input Current (Amp):</b>	0.1683
<b>Input Power (W):</b>	20.02
<b>Input Power Factor:</b>	0.9908
<b>Current ATHD (%):</b>	11.1%

### Test Condition

<b>Ambient Temperature (°C):</b>	25.0
<b>Stabilization Time (Hours):</b>	0:35
<b>Total Operating Time (Hours):</b>	1:20




FIG. 1 LUMINAIRE

## Test Methods

### Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

### Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

### Disclaimers:

This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of Federal Government.

Report Prepared by : Keyur Patel

Test Report Reviewed by:



Steve Kang  
Quality Assurance

*\*Attached are photometric data reports. Total number of pages: 11*



8165 E. Kaiser Blvd. Anaheim, CA 92808  
www.lightlaboratory.com

# Photometric Test Report

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : L022111005.IES**

## DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002  
[TEST] L022111005  
[TESTLAB] LIGHT LABORATORY, INC. (www.lightlaboratory.com)  
[ISSUEDATE] 2/22/2021  
[MANUFAC] Light and Green  
[LUMCAT] LG-1042-27K  
[LUMINAIRE] Surface Mount Wall Sconce  
[BALLASTCAT] ERP EBR020U-0500-42  
[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND  
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.  
[INPUT] 120.02VAC, 20.02W  
[TEST PROCEDURE] IESNA:LM-79-08

## CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1088
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	54
Total Luminaire Watts	20.02
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Hor. Cylinder Along Length
Luminous Length (0-180)	0.01 ft
Luminous Width (90-270)	0.77 ft (Diameter)
Luminous Height	0.77 ft (Diameter)

## LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	122	227	23686
55	111	148	22932
65	104	126	22639
75	98	122	22080
85	95	121	21787

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
<b>0</b>	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44
<b>5</b>	15.61	15.63	15.67	15.73	15.81	15.90	16.02	16.16	16.31	16.47
<b>10</b>	12.99	13.02	13.08	13.19	13.33	13.51	13.73	13.99	14.28	14.60
<b>15</b>	10.72	10.75	10.82	10.95	11.13	11.37	11.66	11.98	12.35	12.77
<b>20</b>	8.63	8.67	8.77	8.94	9.16	9.45	9.80	10.19	10.62	11.16
<b>25</b>	6.67	6.70	6.82	7.02	7.29	7.64	8.06	8.55	9.10	9.71
<b>30</b>	4.96	5.01	5.15	5.35	5.64	6.01	6.45	6.99	7.64	8.36
<b>35</b>	3.77	3.81	3.92	4.10	4.35	4.66	5.07	5.66	6.32	7.09
<b>40</b>	3.56	3.57	3.59	3.63	3.68	3.76	4.08	4.58	5.19	5.98
<b>45</b>	3.74	3.73	3.69	3.66	3.62	3.58	3.67	3.77	4.34	5.02
<b>50</b>	3.84	3.84	3.82	3.79	3.75	3.69	3.61	3.62	3.76	4.30
<b>55</b>	3.95	3.93	3.92	3.89	3.85	3.80	3.74	3.64	3.62	3.79
<b>60</b>	4.02	4.00	4.00	3.97	3.94	3.88	3.81	3.74	3.62	3.66
<b>65</b>	4.09	4.08	4.06	4.04	3.99	3.95	3.88	3.81	3.70	3.57
<b>70</b>	4.12	4.10	4.09	4.07	4.05	4.01	3.95	3.86	3.76	3.63
<b>75</b>	4.09	4.11	4.11	4.11	4.10	4.06	3.99	3.91	3.80	3.68
<b>80</b>	4.09	4.11	4.12	4.12	4.13	4.08	4.03	3.94	3.84	3.73
<b>85</b>	4.09	4.12	4.12	4.14	4.15	4.13	4.06	3.96	3.86	3.75
<b>90</b>	4.13	4.14	4.17	4.16	4.19	4.14	4.07	3.98	3.90	3.77
<b>95</b>	4.19	4.17	4.18	4.17	4.17	4.15	4.08	3.98	3.89	3.78
<b>100</b>	4.16	4.16	4.19	4.18	4.17	4.13	4.07	3.97	3.88	3.78
<b>105</b>	4.19	4.19	4.18	4.18	4.16	4.12	4.05	3.97	3.87	3.75
<b>110</b>	4.19	4.19	4.18	4.16	4.12	4.08	4.01	3.93	3.85	3.72
<b>115</b>	4.16	4.17	4.14	4.12	4.06	4.00	3.96	3.88	3.77	3.66
<b>120</b>	4.12	4.12	4.09	4.06	4.01	3.96	3.88	3.80	3.68	3.72
<b>125</b>	4.05	4.04	4.01	3.99	3.95	3.88	3.81	3.70	3.68	3.82
<b>130</b>	3.95	3.94	3.91	3.89	3.84	3.78	3.70	3.70	3.82	4.32
<b>135</b>	3.81	3.82	3.80	3.77	3.72	3.67	3.76	3.86	4.40	5.06
<b>140</b>	3.70	3.70	3.72	3.77	3.82	3.88	4.20	4.68	5.28	6.10
<b>145</b>	3.98	4.00	4.10	4.29	4.55	4.88	5.28	5.83	6.47	7.24
<b>150</b>	5.20	5.26	5.40	5.60	5.88	6.21	6.62	7.15	7.78	8.49
<b>155</b>	6.99	7.02	7.13	7.29	7.52	7.82	8.21	8.67	9.22	9.84
<b>160</b>	8.98	8.98	9.04	9.16	9.35	9.60	9.93	10.32	10.77	11.34
<b>165</b>	10.90	10.92	10.99	11.12	11.31	11.56	11.85	12.20	12.59	13.02
<b>170</b>	13.27	13.30	13.36	13.47	13.61	13.79	14.01	14.26	14.55	14.86
<b>175</b>	15.96	15.97	16.00	16.05	16.12	16.21	16.32	16.45	16.59	16.74
<b>180</b>	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00

Vert. Horizontal Angles  
 Angles

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>	<u>95</u>
<b>0</b>	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44
<b>5</b>	16.65	16.84	17.04	17.26	17.48	17.70	17.94	18.17	18.41	19.35
<b>10</b>	14.96	15.34	15.75	16.16	16.59	17.04	17.49	17.95	18.41	20.27
<b>15</b>	13.25	13.83	14.43	15.06	15.75	16.35	16.99	17.64	18.30	21.06
<b>20</b>	11.78	12.44	13.15	13.97	14.81	15.71	16.50	17.35	18.20	21.78
<b>25</b>	10.38	11.16	12.03	12.93	13.91	14.92	15.95	16.98	18.02	22.43
<b>30</b>	9.15	10.01	10.92	11.96	13.04	14.20	15.39	16.56	17.74	22.97
<b>35</b>	7.97	8.91	9.82	10.82	12.00	13.29	14.68	16.09	17.52	23.44
<b>40</b>	6.78	7.69	8.58	9.53	10.81	12.28	13.95	15.61	17.24	23.85
<b>45</b>	5.77	6.53	7.33	8.31	9.58	11.31	13.21	15.11	16.96	24.25
<b>50</b>	4.91	5.54	6.22	7.08	8.34	10.30	12.42	14.57	16.59	24.68
<b>55</b>	4.25	4.75	5.34	5.95	7.28	9.24	11.55	14.00	16.42	25.18
<b>60</b>	3.83	4.11	4.56	5.06	6.25	8.27	10.86	13.58	16.33	25.70

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : L022111005.IES**

**CANDELA TABULATION - (Cont.)**

<b>65</b>	3.61	3.74	3.95	4.32	5.33	7.40	10.28	13.22	16.21	26.15
<b>70</b>	3.54	3.50	3.53	3.71	4.49	6.63	9.73	12.80	16.07	26.55
<b>75</b>	3.54	3.42	3.32	3.26	3.81	5.87	9.16	12.40	15.81	26.77
<b>80</b>	3.57	3.44	3.25	3.09	3.50	5.31	8.59	11.99	15.61	27.09
<b>85</b>	3.62	3.50	3.24	3.07	3.49	5.09	8.27	11.58	15.60	27.28
<b>90</b>	3.65	3.51	3.23	3.06	3.51	5.01	8.10	11.42	15.65	27.51
<b>95</b>	3.66	3.52	3.26	3.08	3.53	5.10	8.13	11.49	15.72	27.65
<b>100</b>	3.65	3.48	3.25	3.12	3.56	5.34	8.44	11.92	15.81	27.82
<b>105</b>	3.62	3.48	3.32	3.28	3.82	5.84	9.09	12.37	15.95	27.52
<b>110</b>	3.62	3.55	3.53	3.68	4.44	6.60	9.73	12.84	16.09	27.16
<b>115</b>	3.68	3.75	3.95	4.31	5.32	7.41	10.33	13.32	16.22	26.73
<b>120</b>	3.88	4.13	4.55	5.06	6.30	8.36	10.98	13.69	16.35	26.27
<b>125</b>	4.27	4.77	5.35	5.95	7.40	9.37	11.67	14.11	16.52	25.82
<b>130</b>	4.90	5.56	6.30	7.19	8.51	10.42	12.47	14.58	16.70	25.36
<b>135</b>	5.81	6.56	7.43	8.45	9.74	11.43	13.27	15.13	16.96	24.90
<b>140</b>	6.91	7.77	8.65	9.61	10.90	12.37	14.03	15.66	17.26	24.45
<b>145</b>	8.10	9.00	9.88	10.87	12.08	13.40	14.80	16.18	17.55	23.99
<b>150</b>	9.27	10.11	11.00	12.04	13.12	14.29	15.49	16.67	17.88	23.43
<b>155</b>	10.50	11.28	12.16	13.08	14.06	15.09	16.11	17.10	18.11	22.74
<b>160</b>	11.97	12.64	13.35	14.15	14.97	15.85	16.63	17.45	18.29	21.95
<b>165</b>	13.52	14.07	14.65	15.27	15.95	16.53	17.16	17.80	18.44	21.18
<b>170</b>	15.20	15.57	15.96	16.36	16.78	17.22	17.66	18.11	18.57	20.41
<b>175</b>	16.92	17.10	17.29	17.50	17.71	17.93	18.16	18.39	18.62	19.55
<b>180</b>	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00

**Vert. Angles**      **Horizontal Angles**

	<b>100</b>	<b>105</b>	<b>110</b>	<b>115</b>	<b>120</b>	<b>125</b>	<b>130</b>	<b>135</b>	<b>140</b>	<b>145</b>
<b>0</b>	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44	18.44
<b>5</b>	20.29	21.22	22.12	23.00	23.84	24.64	25.40	26.10	26.75	27.33
<b>10</b>	22.12	23.95	25.73	27.47	29.18	31.87	34.47	36.89	39.11	41.11
<b>15</b>	23.80	26.50	29.29	33.82	38.19	42.35	46.27	50.44	54.63	58.42
<b>20</b>	25.36	29.02	35.25	41.30	47.13	53.92	60.47	66.58	72.23	77.43
<b>25</b>	26.83	33.33	41.04	48.83	57.89	66.56	74.82	82.64	89.88	96.48
<b>30</b>	28.23	37.45	46.58	57.62	68.46	78.97	88.99	98.45	107.32	115.42
<b>35</b>	30.58	41.29	53.10	66.03	78.72	91.02	102.82	114.01	124.29	133.59
<b>40</b>	32.89	44.93	59.41	74.08	88.57	102.64	116.18	128.72	140.41	151.48
<b>45</b>	35.06	48.85	65.32	81.74	97.90	113.73	128.33	142.41	155.60	168.83
<b>50</b>	37.17	52.95	70.89	88.90	106.45	123.21	138.45	153.90	170.00	187.55
<b>55</b>	39.09	56.69	76.00	95.18	113.18	130.15	147.59	165.54	187.09	208.76
<b>60</b>	40.84	59.95	79.92	99.31	118.00	136.81	158.00	181.04	205.56	230.68
<b>65</b>	42.22	62.07	82.14	102.71	123.96	145.99	169.41	195.25	222.54	253.95
<b>70</b>	43.08	63.14	84.46	107.27	130.58	154.08	179.51	207.65	238.38	273.35
<b>75</b>	43.24	64.49	87.79	112.23	135.91	159.90	187.29	217.53	252.55	287.14
<b>80</b>	43.83	66.56	91.00	115.88	139.61	164.05	192.92	224.68	262.73	297.41
<b>85</b>	44.92	68.69	93.57	118.01	141.84	166.72	196.33	228.79	269.17	303.89
<b>90</b>	45.35	69.52	94.04	118.79	142.68	167.73	197.34	229.72	271.58	306.27
<b>95</b>	45.81	69.83	94.14	118.36	142.17	166.95	195.84	227.97	269.61	304.46
<b>100</b>	45.56	68.82	92.68	116.84	140.36	164.50	192.15	223.52	263.31	298.64
<b>105</b>	44.94	67.55	90.82	114.39	137.45	160.53	186.48	216.32	252.82	288.76
<b>110</b>	44.04	65.75	88.36	111.15	133.44	155.08	178.78	206.69	238.52	275.39
<b>115</b>	42.86	63.49	85.26	107.11	128.30	148.33	169.15	194.93	222.86	255.45
<b>120</b>	41.48	60.78	81.51	102.20	122.38	140.03	159.44	182.33	206.84	232.00
<b>125</b>	39.91	57.63	77.14	96.56	115.26	131.72	149.24	168.35	189.79	211.49
<b>130</b>	38.11	54.06	72.21	90.18	106.69	122.11	138.36	155.36	172.47	190.52
<b>135</b>	36.12	50.12	66.76	82.86	97.95	111.57	126.73	141.77	156.13	169.80

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : L022111005.IES**

**CANDELA TABULATION - (Cont.)**

<b>140</b>	33.91	46.15	60.66	74.88	87.57	100.56	114.61	127.92	140.07	151.52
<b>145</b>	31.54	42.34	53.96	66.24	77.65	88.72	101.17	113.37	124.16	133.57
<b>150</b>	29.00	38.16	47.15	57.35	67.31	77.52	87.89	97.96	107.29	115.50
<b>155</b>	27.33	33.73	41.13	48.56	57.12	65.43	73.82	82.21	89.87	96.72
<b>160</b>	25.59	29.30	35.27	41.09	46.73	53.48	60.11	66.39	72.22	77.58
<b>165</b>	23.91	26.60	29.36	33.80	38.08	42.17	46.04	50.25	54.59	58.50
<b>170</b>	22.24	24.05	25.82	27.53	29.22	31.89	34.49	36.91	39.15	41.19
<b>175</b>	20.47	21.38	22.27	23.13	23.95	24.74	25.48	26.17	26.80	27.38
<b>180</b>	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00

**Vert. Horizontal Angles**

	<b>150</b>	<b>155</b>	<b>160</b>	<b>165</b>	<b>170</b>	<b>175</b>	<b>180</b>
<b>0</b>	18.44	18.44	18.44	18.44	18.44	18.44	18.44
<b>5</b>	27.85	28.29	28.66	28.95	29.33	29.33	29.34
<b>10</b>	42.88	44.41	45.67	46.67	47.40	47.98	47.99
<b>15</b>	61.76	64.65	67.04	68.94	70.31	71.41	71.43
<b>20</b>	82.04	86.02	89.33	91.95	93.86	95.42	95.46
<b>25</b>	102.39	107.52	111.81	115.24	117.73	119.22	119.73
<b>30</b>	122.57	128.68	133.80	137.86	140.78	142.55	143.14
<b>35</b>	141.94	149.56	156.02	161.14	164.84	167.08	167.83
<b>40</b>	161.71	171.33	180.34	187.69	193.17	196.58	197.73
<b>45</b>	182.54	194.95	207.20	217.02	224.33	228.71	230.21
<b>50</b>	205.07	221.72	237.85	252.56	263.43	270.15	272.40
<b>55</b>	230.13	253.83	274.15	287.87	298.19	304.46	306.60
<b>60</b>	259.37	283.27	302.46	314.91	323.41	328.68	330.49
<b>65</b>	283.28	307.32	322.66	334.17	341.34	345.93	347.50
<b>70</b>	302.21	322.72	337.64	348.52	355.52	360.19	361.82
<b>75</b>	314.46	334.17	348.47	359.13	366.74	371.48	373.35
<b>80</b>	323.25	341.56	355.64	366.74	374.83	379.50	381.45
<b>85</b>	328.90	346.63	360.76	371.77	379.63	384.24	386.20
<b>90</b>	331.01	348.85	363.04	374.06	381.97	386.76	388.39
<b>95</b>	329.48	347.55	361.81	372.81	380.57	385.25	387.25
<b>100</b>	324.58	343.20	357.45	368.40	376.23	380.68	382.50
<b>105</b>	316.49	336.22	350.59	361.14	368.52	373.16	374.88
<b>110</b>	304.56	324.93	339.90	350.87	357.91	362.56	364.23
<b>115</b>	285.53	309.97	325.42	337.10	344.34	348.89	350.57
<b>120</b>	261.60	285.96	305.59	318.12	326.71	332.09	333.98
<b>125</b>	232.61	256.52	276.93	291.07	301.60	308.20	310.41
<b>130</b>	208.13	224.59	240.78	255.65	266.75	273.69	276.07
<b>135</b>	184.27	197.05	209.16	219.11	226.54	231.12	232.69
<b>140</b>	161.89	171.63	180.91	188.39	193.91	197.29	198.46
<b>145</b>	141.97	149.59	156.04	161.18	164.94	167.22	167.97
<b>150</b>	122.67	128.74	133.80	137.81	140.70	142.48	143.10
<b>155</b>	102.59	107.67	111.90	115.24	117.64	119.11	119.59
<b>160</b>	82.30	86.28	89.57	92.15	94.01	95.51	95.49
<b>165</b>	61.95	64.90	67.35	69.26	70.62	71.71	71.71
<b>170</b>	43.00	44.55	45.85	46.87	47.62	48.24	48.27
<b>175</b>	27.88	28.32	28.68	28.96	29.33	29.34	29.34
<b>180</b>	18.00	18.00	18.00	18.00	18.00	18.00	18.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : L022111005.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	11.09	N.A.	1.00
0-30	31.47	N.A.	2.90
0-40	67.31	N.A.	6.20
0-60	201.41	N.A.	18.50
0-80	417.51	N.A.	38.40
0-90	542.09	N.A.	49.80
10-90	539.96	N.A.	49.60
20-40	56.22	N.A.	5.20
20-50	111.66	N.A.	10.30
40-70	234.25	N.A.	21.50
60-80	216.10	N.A.	19.90
70-80	115.96	N.A.	10.70
80-90	124.57	N.A.	11.50
90-110	241.57	N.A.	22.20
90-120	342.73	N.A.	31.50
90-130	422.35	N.A.	38.80
90-150	514.06	N.A.	47.30
90-180	545.61	N.A.	50.20
110-180	304.04	N.A.	28.00
0-180	1087.7	N.A.	100.00

Total Luminaire Efficiency = N.A.%

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	2.13
10-20	8.96
20-30	20.38
30-40	35.84
40-50	55.44
50-60	78.66
60-70	100.14
70-80	115.96
80-90	124.57
90-100	124.86
100-110	116.71
110-120	101.16
120-130	79.62
130-140	55.85
140-150	35.87
150-160	20.41
160-170	9.00
170-180	2.14



**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : L022111005.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
	RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	
0	107	107	107	107	99	99	99	99	83	83	83	69	69	69	56	56	56	50
1	92	85	79	73	84	78	72	67	64	60	56	52	48	46	40	38	36	30
2	81	71	63	55	74	65	57	51	53	47	42	42	38	34	32	29	26	21
3	73	61	51	44	66	55	47	40	45	38	33	35	30	26	27	23	19	15
4	66	52	43	35	59	48	39	32	39	32	26	31	25	21	23	19	15	11
5	60	46	36	29	54	42	33	27	34	27	22	27	21	17	20	16	12	9
6	55	41	31	24	50	37	29	22	30	23	18	24	18	14	18	14	10	7
7	50	36	27	21	46	33	25	19	27	20	16	21	16	12	16	12	9	6
8	47	33	24	18	42	30	22	16	24	18	13	19	14	10	14	10	7	5
9	43	30	21	16	39	27	19	14	22	16	12	18	13	9	13	9	6	4
10	40	27	19	14	37	25	17	13	20	14	10	16	11	8	12	8	6	3


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : L022111005.IES**

**UGR TABLE - CORRECTED**

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	0.3	0.3	0.3	0.3	0.3	6.7	7.7	7.6	8.7	10.0
	3H	0.3	0.3	0.3	0.3	0.3	8.0	9.0	8.9	9.9	11.2
	4H	0.3	0.3	0.3	0.3	1.2	8.5	9.4	9.4	10.4	11.7
	6H	0.3	1.0	1.1	2.0	3.3	8.9	9.7	9.8	10.7	12.0
	8H	1.2	2.0	2.2	3.0	4.3	9.0	9.9	10.0	10.9	12.2
	12H	2.4	3.2	3.4	4.2	5.5	9.2	10.0	10.2	11.0	12.3
4H	2H	0.3	0.3	0.3	0.3	0.3	11.6	12.5	12.5	13.5	14.7
	3H	0.3	0.3	0.3	0.3	0.3	13.2	14.0	14.1	15.0	16.3
	4H	0.3	0.3	0.3	0.3	1.5	13.8	14.6	14.8	15.6	16.9
	6H	0.6	1.3	1.6	2.3	3.6	14.3	15.0	15.3	16.0	17.3
	8H	1.8	2.4	2.8	3.4	4.8	14.4	15.1	15.4	16.1	17.4
	12H	3.1	3.7	4.1	4.7	6.0	14.5	15.1	15.5	16.1	17.5
8H	4H	0.3	0.3	0.3	0.3	1.5	17.3	17.9	18.2	18.9	20.2
	6H	0.8	1.4	1.8	2.4	3.8	18.0	18.5	19.0	19.6	20.9
	8H	2.1	2.6	3.1	3.6	5.0	18.2	18.7	19.2	19.8	21.1
	12H	3.5	3.9	4.5	4.9	6.3	18.4	18.9	19.4	19.9	21.3
12H	4H	0.3	0.3	0.3	0.3	1.5	18.4	19.0	19.4	20.0	21.3
	6H	0.8	1.4	1.8	2.4	3.8	19.3	19.8	20.3	20.8	22.2
	8H	2.1	2.6	3.1	3.6	5.0	19.7	20.1	20.7	21.2	22.6

Maximum UGR = 22.6

POLAR GRAPH



Maximum Candela = 388.39 Located At Horizontal Angle = 180, Vertical Angle = 90  
# 1 - Vertical Plane Through Horizontal Angles (180 - 0) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (90) (Through Max. Cd.)