


# LG-5010

## Adjustable Spot Head for Knife Edge



|                      |               |
|----------------------|---------------|
| Project Information: | Project Name: |
| Fixture Type:        | Location:     |

## KNIFE EDGE

### Spot Head Lighting

Revolutionary spot head lighting attachment for Knife Edge invisible track light rail system. This versatile spot head has a full range of mobility and is field changeable, allowing for placement adjustments throughout the rail system.

LED lighting engine is high performance, low power that provides outstanding reliability and color quality/consistency. 2700K, 3000K, 3500K, 4000K color temperatures are available with 95 CRI.

- Fixtures are offered with a choice of spot, narrow flood or flood beam pattern
- Life Rated for 40,000 hours at 70% lumen maintenance
- All testing reports are based on published industry procedures



## Quick Info

|  |   |
|--|---|
| <b>Application</b><br>New Construction / Remodeling                                      |   |
| <b>Delivered Lumens</b><br>1500 lm (15W) / 3200lm (40W - RGBW only)                      | <b>Color Quality</b><br>95 CRI, 2-step SDCM   |
| <b>Color Temperature</b><br>2700K<br>3000K<br>3500K<br>4000K<br>RGBW                     | <b>Light Distribution</b><br>General<br>Wall Wash<br>Spot Light                               |
| <b>Input Voltage</b><br>120/277V   | <b>Dimming</b><br>TRIAC/ ELV  |
| <b>Arm</b><br>Aluminum material / Black powder coating<br>Arm has full range of mobility | <b>Additional Arm Color</b><br>White  |
| <b>Module Ratings</b><br>Damp Location   |   |
| <b>Guarantee</b><br>40,000 hrs   3 years   | <b>Additional Dimming Options</b><br>0-10 / DALI Dimming / Lutron EcoSystem / DMX (RGBW only) |

# LG-5010

## Adjustable Spot Head for Knife Edge

|                      |               |
|----------------------|---------------|
| Project Information: | Project Name: |
| Fixture Type:        | Location:     |

## Ordering Guide

### PRODUCT CODE

LG - 5010

### ARM COLOR

- B - Black (STANDARD)
- W - White

### LED OPTIONS

|   |    |  |
|---|----|--|
| <b>OUTPUT</b> <ul style="list-style-type: none"><li><input type="checkbox"/> CL2-15AR111 - 1500 LUM (15W) (STANDARD)</li></ul>  | OR | <b>OUTPUT (RGBW ONLY)</b> <ul style="list-style-type: none"><li><input type="checkbox"/> CL2-25QLG111 - 25W (RGBW only)</li><li><input type="checkbox"/> CL2-40QLG111 - 3200 LUM 40W (RGBW only)</li></ul> |
| <b>COLOR TEMPERATURE</b> <ul style="list-style-type: none"><li><input type="checkbox"/> 27K - 2700K</li><li><input type="checkbox"/> 30K - 3000K (STANDARD)</li><li><input type="checkbox"/> 35K - 3500K</li><li><input type="checkbox"/> 40K - 4000K</li></ul> |    |  |

### CRI

- 95 - 95 CRI
- 90 - 90 CRI (RGBW only)

### BEAM SPREAD

- 20 °
- 40 ° (STANDARD)

### LENS OPTICAL

- FR - Frosted
- MF - Middle Frosted

### LENS HOLDER

- FLB - Flat Black (STANDARD)
- FLWH - Flat White

### DIMMING OPTION

- T - Triac/ELV (STANDARD)
- D - DALI
- ECO - (Hi - lume Premier 0.1% Eco System LED Driver with Soft-on, Fade-to-black dimming technology)
- 0 - 10
- DMX - DMX512 (For RGBW only)

### Example Number

LG-5010 B CL2-15AR111 30K 95 42 MF FLB T

### Order Number

LG-5010 \_ \_ \_ \_ \_

# LG-5010

Adjustable Spot Head  
for Knife Edge

|                      |               |
|----------------------|---------------|
| Project Information: | Project Name: |
| Fixture Type:        | Location:     |

## ACCESSORIES



Frosted



Middle Frosted



Flat (Black or White)




20° Light Beam



40° Light Beam


OPTIONAL ELECTRICIFIED CHANNEL AVAILABLE, SEE [LG-5008E](#) / [LG-5008F](#) SPEC SHEETS FOR MORE DETAIL




# LG-5010

## Wiring Diagrams For Knife Edge


### PER FIXTURE REMOTE DRIVER INSIDE COVE



### PER MULTIPLE FIXTURES REMOTE DRIVER INSIDE THE COVE




### PER MULTIPLE FIXTURES REMOTE DRIVER OUTSIDE THE COVE



# LG-5010

Adjustable Spot Head  
for Knife Edge

## ARM + LED LAMP



|                      |               |
|----------------------|---------------|
| Project Information: | Project Name: |
| Fixture Type:        | Location:     |



| LED TYPE  | CL2-15AR111  | CL2-25QLG111                     | CL2-40QLG111 |
|---|--|----------------------------------|--------------|
| DELIVERED LUMENS                                  | 1500   | 2200                             | 3200         |
| WATTS   | 15W  | 25                               | 40W          |
| CRI   | 95   | 90                               | 90           |
| CRI OPTION  | 2700K / 3000K / 35000K / 4000K   | RGBW                             | RGBW         |
| VOLTAGE   | 120V / 277V  |                                  |              |
| DIMMING   | <ul style="list-style-type: none"> <li>• TRIAC /ELV Standard (Down to &gt; 1%) - STANDARD</li> <li>• 0 -10 v (Down to &gt; 5%)</li> <li>• Lutron (Hi-lume Premier 0.1 % Eco System LED Driver with Soft-on, Fade-to-black dimming technology)</li> <li>• DALI</li> <li>• DMX   DMX512 (for RGBW only)</li> </ul> |                                  |              |
| POWER SUPPLY<br>(Installed remote or inside cove) | Constant current driver<br>36Vdc /350mA  | Constant current driver<br>48Vdc |              |
| BEAM SPREAD                                       | 11°/17°/26°/42°  | 16°/20°                          |              |
| OPTICS  | Frosted / Middle Frosted   |                                  |              |
| ADJUSTABILITY                                     | Adjustable - 360°, full range of mobility  |                                  |              |
| FINISH  | Aluminum Powder Coating  |                                  |              |

### Product Features

- Revolutionary spot head lighting with full range of adjustability
- Energy efficient LED light engines
- Versatile field changeable optics
- Dimmable with a variety of commonly used drivers
- Fixtures can be used with all Smart House Systems such as Lutron, Vantage, Control4, Crestron and others
- Easy installation for new construction and remodel applications
- Class 2
- UL approved fixtures
- Standard driver included