


LG-4008

Wall Recessed Sconce



Quick Info



Application New Construction / Remodeling	
Delivered Lumens 460 lm (9W)	Color Quality 80 CRI, 2-step SDCM
Color Temperature 3000K	Light Distribution Stairway Pathway
Input Voltage 120V / 277V	Beam Spread 120°
Trims Gypsum Flangeless (seamless)	Dimming TRIAC/ ELV or 0-10
Housing Ratings N/A	Module Ratings  Damp Location
Guarantee 40,000 hrs 3 years	

Project Information:	Project Name:
Fixture Type:	Location:

HARMONY

Recessed LED Wall Sconce

Harmony recessed LED wall sconces are solid plaster lighting solutions made from gypsum, an abundant and stable mineral found in the Earth's crust. Our wall sconce is paintable, texturable, and manufactured at the highest possible level 5 plaster finish. Designed with a SMD LED that is high performance, low power that provides outstanding reliability and color quality/consistency. 3000K color temperature is available with 80 CRI.

- Revolutionary flush mounted trimless and seamless design which offers consistent aesthetics
- Energy efficient LED light engines
- IC Rated UL approved fixtures
- Environmentally friendly materials
- Internal driver included
- For best results, do not paint the inside of the fixture. If painting is necessary we recommend using a spraying technique. Painting with a brush will reveal brush strokes when illuminated.

LG-4008

Wall Recessed Steplight LED

Project Address:	Project Name:
Fixture Type:	Quantity:

Ordering Guide

Series

-

Color Temperature

-

Dimming

-

CRI

-

Beam Spread

Formula Example:

LG-4008

-

30K

-

T

-

80

-

120°

Series	Color Temperature		Dimming		CRI	Beam Spread
LG-4008	30K	3000K (standard)	T	Triac / ELV (STANDARD)	80	120°
			0-10	0-10		

*REQUIRED: Zone schedule, please include in your request how many lights on each switch leg.

EXAMPLE:

Switch Leg	Fixture Qty
1	12
2	8
3	9
4	5